



TECHNOLOGY PLASMA 60 XT 230V



NEW

Overview

TECHNOLOGY PLASMA 60 XT 230V

cod. 816148

Inverter, compressed air plasma cutting system, with contact striking of pilot arc.

Allows a rapid, distortion-proof cutting, grid cutting and gauging of all conductive materials such as steel, stainless steel, galvanised steel, aluminium, copper, brass, etc.

Features:

- robust and impact resistant;
- reduced weight and dimensions;
- warning led for torch under voltage, protections;
- warning led for consumables change;
- torch automatic cooling;
- visualization of air pressure;
- thermostatic, overvoltage, undervoltage, overcurrent, air failure protections.

Complete with PH torch.



1 PH 230V



CE MARKING



EAC CERTIFICATION

Technical data



CODE 816148



MAX ABSORBED POWER 5,5 kW



MAX CUTTING THICKNESS 20 mm



SINGLE PHASE MAINS VOLTAGE 230 V



MAINS FUSE 20 A



COMPRESSED AIR CAPACITY 100 L/
min



MAINS FREQUENCY 50 / 60 Hz



EFFICIENCY 90 V



COMPRESSED AIR PRESSURE 4 - 5 bar



CURRENT RANGE 10 - 60 A



POWER FACTOR (cosphi) 0,7



MAX CURRENT (EN 60974-1) 50A @ 30
% A



TECHNOLOGY PLASMA 60 XT 230V



PROTECTION DEGREE IP23



MAX NO LOAD VOLTAGE 313 V



DIMENSIONS 50,6 x 18,2 x 29,2 cm



MAX ABSORBED CURRENT 34 A