

Microprocessor controlled MIG-MAG/FLUX/BRAZING/MMA/ TIG DC-Lift inverter multiprocess welding machine. Technomig Dual Synergic is confirmed as the perfect solution for a wide range of applications, from maintenance to installation and interventions in body shops, because of its flexibility and the different materials it can weld (steel, stainless steel, aluminium) or braze weld (galvanized sheet). The quick SYNERGIC regulation of the welding parameters, thanks to the ONE TOUCH LCD SYNERGY technology, makes this product easy to use. The intelligent and automatic control of the arc, moment by moment, maintains high welding performance in all working conditions, with different materials and/or gases. The operator can also intervene manually along the arc length: this adjustment means the weld seam can be modified according to the welder's style. The ONE TOUCH LCD graphic display allows for a better reading of all welding parameters. Lightweight and very compact, Technomig can be moved around easily in all intervention areas, both indoors and outdoors. Main features: polarity reversal for GAS MIG-MAG/BRAZING welding * 17 synergy curves available * visualization on LCD display of voltage, current, welding speed * regulation of: wire speed up slope, electronic reactance, burn-back time, post gas * choice of 2/4 times, spot operation * thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator (+/- 15%) protections. Completewith MIG-MAG torch, work clamp and cable.



PROFESSIONAL



MIG-MAG/TIG/MMA MULTIPROCESS

ONE TOUCH EASY TO SET, EASY TO WORK!
LCD SYNERGY

WELDS FE,SS,AL,GALVANISED SHEETS

MIG-MAG

IMMEDIATE READING OF ALL PARAMETERS

17 PRE-SET SMART CURVES

SYNERGY

SEAM CAN BE SHAPED AS REQUIRED

FINE SET

OPTIONAL: TROLLEY

Norms: LVD: EN 60974-1 EMC: EN 60974-10

 V _{50/60Hz}	 A	 EN60974-1	 EN60974-1	 V	 A	 kW	 n%	 cosphi	 mm
230 1 ph	20 220 DC	180 20% DC	100 DC	78	15 32	2,2 5	84	0,7	0,6 1
 mm	 mm	 mm	 mm	 mm	 IP23	 cm(L,W,H)	 kg	 8004897917 63 4	 pz/pallet
0,8 1	0,8 1	0,8 1,2	0,8 1	1,6 4		62 26 49	22		8